

8RS485 INTERFACE CARD

Features

- * 8-port universal data interface card supports RS232/RS422/RS485 interface
- DCE interface per port
- Per port software configurable
- RS485 supports 4 wires Full Duplex
- RS422 supports 4 wires
- Supports Full-Duplex and Half-Duplex modes (optional)
- * Oversampling channel to transmit ASYNC data
- * $N \times 56/64K$ bps, $N = 1$ to 6 for DS0 channels to oversample the ASYNC data
- * Channel for 56Kbps or 64Kbps is software configurable for each card application
- * Card base options are Omnibus, Terminal Server, and Clock Pass Through functions
- Terminal Server (TS)
- 8 remote IP address for each physical port
- Router Mode: 64WANS, RIP-I, RIP-II, Static route
- Bandwidth for each WAN is $N \times 64Kbps$; $N=1$ to 32
- Omnibus (OMNI)
- Omnibus for data
- Application of Daisy Chain, Star, Point to Multi-point
- Maximum 8 groups/per port
- Clock Pass Through (CPT)
- Pass through RS232 clock transparently for RADAR application
- * Handshaking for RS232 only
- * Flow control for RS232 only
- * Loopback

DESCRIPTION

The 8RS485 card of QX3440 series is 8-port universal data interface card that complies with RS232/RS422/RS485 DCE interface for ASYNC data transmission by oversampling SYNC data channel. It allows multiplexing of $n \times 56/64Kbps$ data to multiply of DS0 time slot onto a digital network.

The 8RS485 card provide oversampling function as basic, it can be set to be Omnibus (OMNI), Terminal Server (TS), or Clock Pass Through (CPT) by card base.



ORDERING INFORMATION

To specify options, choose from list below.

Model	Description
QX3440-8RS485	8 RS232/RS422/RS485 asynchronous interfaces (200-300-600-1.2k-2.4-4.8-9.6-38.4-57.6-115.2-128kbps per oversampling) DCE with RJ45 for QX3440, use 1 long slot
QX3440-8RS485-TS-BUS	8 RS232/RS422/RS485 asynchronous interfaces (200-300-600-1.2k-2.4-4.8-9.6-38.4-57.6-115.2-128kbps per oversampling) DCE with RJ45 for QX3440, use 1 long slot. This version support Terminal server, Omnibus with DNP3 and Modbus protocols.

SPECIFICATIONS

RS232/RS422/RS485 Data Interface Function

Data Port	8 port Universal DTE card
ASYNCR Data Rate	200,300, 600, 1200, 2400, 4800, 9600, 19.2K, 38.4K, 57.6K, 115.2K, 128K bps by oversampling
Data Interface	RS232, RS485, RS422
Connector	RJ48C
Interface	DCE only

Terminal Server Function

Data Port	8 port Terminal Server
ASYNCR Data Rate	600, 1200, 2400, 4800, 9600, 19.2K, 38.4K bps
Data Interface	RS232, RS485, RS422
WAN	64 WANs per card
IP Address	Bandwidth for each WAN is N x 64Kbps; N=1 to 32 Up to 8 remote IP Address per port, when role is client
Router Function	RIP-I, RIP-II, Static Route
Stop bit	1 bit, 1.5 bit and 2 bit software configurable
Parity bit	None, Odd, Even
data bit	5, 6, 7 and 8 bit.
Role	Server, Client
Data Buffer Size	1 to 2048 Byte
Data Buffer Time out	1 to 255 ms

Omnibus Function

Data Port	Eight ports per card
Asynchronous Data Rate	600, 1200, 2400, 4800, 9600, 19.2K, 38.4K bps
Data Interface	RS232, RS485, RS422
Synchronous	Not supported
Connector	RJ45C
Data Length	5, 6, 7, 8
Parity	None, Odd, Even
Stop Bit	1, 1.5, 2
Role	Master, Slave
Data Buffer Size	1~2048 Byte
Data Buffer Timeout	1~255 ms
Application	Daisy Chain, Star, Point to Multipoint

Clock Pass Through Function

Data Port	Eight ports per card
Synchronous Data Rate	
Data Interface	RS232
Connector	RJ45C
Application	Pass through RS232 clock transparently for RADAR application

Smart Solutions for
Smart Networks

www.cxr.com



CXR Anderson Jacobson
Rue de l'Ornette
28410 Abondant - France

T +33 (0) 237 62 87 90
F +33 (0) 237 62 88 01
email: contact@cxr.com

The information contained in this document are provided without warranty and do not constitute a contractual document. In order to improve its products, CXR reserves its right to modify, without notice, any part of this document and the specification it contains.

SPECIFICATIONS

Flow Control

Hardware (RS232 only)

Oversampling: RTS and DTR Active and Permanent

Software

Omnibus: RTS Active and Permanent

Terminal Server: Enable and Disable

Loopback

Loopback function To DTE loopback

To Local loopback

LED Indicator

Multi LED indicators ACT: green-power on; red-alarm exist
TS: green-mode is terminal server
X.50 (Omni): green-mode is omnibus
Over Sampling: green-mode is over sampling

Smart Solutions for
Smart Networks

www.cxr.com



CXR Anderson Jacobson
Rue de l'Ornette
28410 Abondant - France

T +33 (0) 237 62 87 90
F +33 (0) 237 62 88 01
email: contact@cxr.com

The information contained in this document are provided without warranty and do not constitute a contractual document. In order to improve its products, CXR reserves its right to modify, without notice, any part of this document and the specification it contains.