

RTDI-415

4G-LTE SECURED ROUTER WITH MODEM AND DIAL-UP INTERFACE



4G / LTE

POTS MODEM

SECURED

VPN Firewall
HW&SW Secure-Boot

RUGGEDIZED

Extended temperature
High EMI

Description

RTDI-415 4G/LTE Router is a highly reliable and secured wireless communication gateway designed for industrial networking. It supports multiband connectivity including GSM, WCDMA and **LTE FDD** for a wide range of applications and vertical machine-to-machine (M2M) and Internet of Things (IoT) markets.

RTDI-415 is especially aimed at serving the migration of Plain Old Telephone Systems and long lasting voice frequency modem communications. **RTDI-415** embeds a **FXS interface and a multimode V21-V34 modem** that emulate the Public Switched Telephone network over 4G/LTE.

RTDI-415 delivers flexible connectivity to multiple applications over **Ethernet, FXS - modem**.

Built for secure and uninterrupted operation in harsh environments, **RTDI-415** supports extended operating temperature from -20 to 70°C and a flexible input voltage range of 12-48V DC. **CXR RTDI-415** series is an ideal cellular communications solution for mission critical networks.

Applications

RTDI-415 is an ideal 4G-LTE Mobile Network gateway to the following networking requirements :

- Electricity, Water, Oil and Gas Utility substations : thanks to its embedded POTS interface and modem to connect long lasting systems (RTU etc.) from their Modem, Serial and Ethernet communication interfaces through the IP and 4G-LTE Cellular networks
- Transport and Smart City infrastructures : thanks to its versatile interfaces to traffic controller, message display, gate control, traffic counters, etc.
- Security sensitive networks : thanks to its security features - VPN, ACL, firewall, 802.1X authentication, Radius and TACACS authentications, PKI, but also extended security mechanisms including Secure-Boot and hardware coded security.

Specifications

4G/LTE Network	
Standards	<ul style="list-style-type: none"> LTE FDD: B1/B3/B5/B7/B8/B20 WCDMA: B1/B5/B8 GSM: 850/900/1800/1900 MHz
Physical	<ul style="list-style-type: none"> 1 or 2x SIM cards 2x SMA connectors
Ethernet Interfaces	
RTDI-415	<ul style="list-style-type: none"> 1x LAN 10/100 BaseT
PSTN modem	
PSTN Interface	<ul style="list-style-type: none"> FXS, 600 Ohms
Modem	<ul style="list-style-type: none"> V21, V22, V22Bis, V23, V32, V32Bis, V34 V42, V42Bis, NMP4-5
Protocoles	
Routing	<ul style="list-style-type: none"> IP v4, IP v6, dual stack NAT
VPN	<ul style="list-style-type: none"> OpenVPN IPSec
Security	<ul style="list-style-type: none"> Firewall ACL, MAC and IP filtering, DMZ Secure-Boot, PKi
Others	<ul style="list-style-type: none"> DNS DynDNS SNTP QoS DHCP Server, Client, Relay UPnP SMS Alarm

General Characteristics	
Format	<ul style="list-style-type: none"> Compact metallic enclosure IP-40 protection DIN rail mounting 19" kit (option)
Dimensions	<ul style="list-style-type: none"> 150 x 103 x 32 mm
Weight	<ul style="list-style-type: none"> 0.7 kg
Operating temp.	<ul style="list-style-type: none"> -20 °C to +70 °C
Hygrometry	<ul style="list-style-type: none"> 10 to 95% HR
Power supply	<ul style="list-style-type: none"> 12-48 Vdc 7 W max
Environment	<ul style="list-style-type: none"> EN-61000-6-2, EN-61000-6-4, IEC-61850-5 EN-60950
Other Interfaces	
Serial Communication	<ul style="list-style-type: none"> Async to UDP / TCP conversion
Administration	
Protocols	<ul style="list-style-type: none"> http, https, ssh, snmp v3, syslog
Management	<ul style="list-style-type: none"> Web interface 2x firmware memory banks NTP
Light indicators	<ul style="list-style-type: none"> Ethernet Link & Activity
Local interface	<ul style="list-style-type: none"> 1x USB Host & Device



Product References

Reference	4G-LTE	GNSS	Ethernet	FXS	RS232/485	DI / DO
RTDI-415	1	-	1	1	-	-



CXR Networks
T +33 (0) 237 62 87 90

17, Rue de l'Ornette 28410 Abondant France
contact@cxr.com www.cxr.com